

FEATURES & BENEFITS

OPTIONS

For more information, visit www.hawsco.com or call (888) 640-4297.




SPECIFICATIONS

The Portable Eyewash Heat Shield is designed to keep water at safe temperatures in warm environments, preventing overheating and ensuring reliable emergency eye protection. Compatible with the Haws 7501 Portable Eyewash, this advanced thermal barrier reduces conductive heat transfer by up to 98% and reflects up to 60% of solar radiation—three times more than an uncovered unit. Built with six layers of heat protection, including waterproof and UV-resistant vinyl fabric, foam insulation, thermal bubble layers, an air gap, and high-density polyethylene, it delivers superior durability and performance for workplace safety.

APPLICATIONS

WARNING: EVEN WITH THE THERMAL JACKET IN PLACE, MANY FACTORS CAN ULTIMATELY AFFECT THE WATER TEMPERATURE WITHIN THE EYEWASH. AS SUCH, HAWS CANNOT GUARANTEE THAT THE THERMAL JACKET WILL PROVIDE A TEPID EYEWASH WATER TEMPERATURE. IT IS THE CUSTOMER'S RESPONSIBILITY TO ENSURE THAT THE WATER STORED WITHIN THE EYEWASH DOES NOT GET DANGEROUSLY HOT OR COLD. HAWS RECOMMENDS TEMPERATURE VERIFICATION OF THE EYEWASH WATER ACROSS THE RANGE OF EXPECTED ENVIRONMENTAL CONDITIONS, AND ADJUSTMENT OF THE EYEWASH INSTALLATION, IF NEEDED, TO FURTHER ENSURE AN ACCEPTABLE EYEWASH WATER TEMPERATURE.




STEP 1:
UNPACK THE JACKET AND LAY FLAT WITH INNER SURFACE (SILVER) UP.


STEP 2:
SET THE 7501 TANK BOTTOM DOWN ON THE JACKET IN THE ORIENTATION SHOWN.




STEP 3:
WRAP THE JACKET UP AND OVER THE 7501 TANK AND ATTACH THE BOTTOM VELCRO CLOSURES.

STEP 4:
SET THE 7501 TANK AND JACKET UPRIGHT. FOLD THE FLAPS OVER THE SIDES OF THE TANK USING THE VELCRO TO ATTACH THE EDGES TOGETHER.




		1455 KLEPPE LANE SPARKS, NEVADA 89431	
Since 1906		(775) 399-4712 FAX (775) 389-7424	
		E-MAIL: HAWS@HAWS.CO.COM	
		WEBSITE: WWW.HAWS.CO.COM	
ENCL: 6176	REV. ENCL: 6176	BY: JIG	MODEL(S) 9126
DRAWN: 01/06/25	DATE: 01/06/25	CHKD: JS	
APPROVED: 02/06/25	DATE: 02/06/25	SCALE: 1:18	DRAWING TYPE: INSTALLATION
		SIZE: A	SHEET 1 OF 2
		PART NUMBER 0510002282	
		REVISION 1	



STEP 5:
 PULL DOWN/OPEN THE EYEWASH FLAP AND THE YELLOW EYEWASH ARM
 ATTACH THE WEBBING LOOP AROUND THE EYEWASH ARM BELOW THE EYEWASH HEADS.

STEP 6:
 MOUNT THE ASSEMBLED EYEWASH AND JACKET IN ACCORDANCE WITH 7501/7501T INSTALLATION INSTRUCTIONS.

		1455 KLEPPE LANE SPARKS, NEVADA, 89431	
Since 1906		(775) 359-4712 FAX (775) 359-7424	
		E-MAIL: HAWS@HAWSCCO.COM	
		WEBSITE: WWW.HAWSCCO.COM	
EN: 6178	REV. EN: 6178	BY: JIG	MODEL(S) 9126
DRAWN: JIG	DATE: 01/26/21	CHKD: JIG	
APPROVED: JIG	DATE: 02/05/25	SCALE: 1:10	DRAWING TYPE: INSTALLATION
		SIZE: A	SHEET 2 OF 2
		PART NUMBER 0510002282	
		REVISION 1	